

Make the smart switch! 1300 DEXTON

Enclosure

Little plugs (caps) must be fitted over fixing screws PRIOR to ENERGISING. The enclosure provided by DEXTON for its range of switches has robust construction and designed to prevent any emission of excessive arcs, flame, molten metal or hot particles. Insulated Plates are: DXWS1/V, DXWS1/P, DXWS2/V, DXWS2/P, DXWS3/V, DXWS3/P, DXWS4/V, DXWS4/P, DXWS5/V, DXWS5/P, DXWS6/V, DXWS6/P, DXWGPO1, DXWGPO1X, DXWGPO2, DXWGPO2X, DXWGPO1/15, DXWGPO2/15, DXWS/RJ11, DXWS/RJ45, DXWS/TVC, DXWS/TVF

Actuating Mechanism

The actuating mechanism is constructed for the switch contacts remain only in the completely closed or the completely open position when the switch is operated in the normal manner.

Insulation resistance between the mechanism and live parts or between the terminals in the 'on' and 'off' position is 500 $M\Omega$

Earthing

The resistance between any earthing terminal or facility and the exposed metal of the switch is $\leq 0.06~\Omega$

Screws

The screwed components are tightened and loosened in a steady and uniform manner of 5 times.

Terminal screw diameter 2.86 mm, torque 0.5 Nm, times 5.

Markings

It is marked in accordance with AS/NZS 3100 with the following information:

- "DEXTON" the registered Trade Mark
- "250V" the operating voltage
- "10A" the current rating
- "AC" Alternating current
- "A" for Active pole
- "N" for Neutral pole
- "E" for Earthing terminal



Make the smart switch! **1300 DEXTON**

PRODUCT SPECIFICATION SHEET

DEXTON ELECTRICAL FLUSH TYPE WALL SWITCHES

A-SERIES

Description

This product is certified to the relevant requirements of AS/NZS 3133:2008 Inc. A1:2009

Trade mark: DFXTON

Product class: Wall Switch

Code: DXWS1/V, DXWS1/P, DXWS2/V, DXWS2/P, DXWS3/V, 1 gang no switch mechs DXWS3/P, DXWS4/V, DXWS4/P, DXWS5/V, DXWS5/P, DXWS6/V, DXWS6/P, DXWGPO1, DXWGPO1X, DXWGPO2, DXWGPO2X, DXWGPO1/15, DXWGPO2/15, DXWS/RJ11,

DXWS/RJ45, DXWS/TVC, DXWS/TVF


Flush type, single pole, two-way wall switches 1, 2, 3, 4, 5 or 6 gang with Polycarbonate or stainlesssteel flush plate. Input: 250 V AC, 16 A



Part No.:DXWS1/V 16amp one gang two way switch Part No.:DXWS1/P



Part No.:DXWS3/V 16amp three gang two way switch Part No.:DXWS3/P



Part No.:DXWS2/V 16amp two gang two way switch

Part No.:DXWS2/P 2 gang no switch mechs



Part No.:DXWS4/V 16amp four gang two way switch Part No.:DXWS1/P 4 gang no switch mechs



3 gang no switch mechs

Part No.:DXWS5/V 16amp five gang two way switch Part No.:DXWS1/P 5 gang no switch mechs



Part No.:DXWS6/V 16amp six gang two way switch Part No.:DXWS1/P 6 gang no switch mechs

Materials

DEXTON switches consist of the followings:

- Plate made of the incombustible PC (PolyCarbonate)
- Metallic plate made of Stainless Steel
- **Terminals made of brass**
- Screws made of steel
- Springs type 75A/φ0.55

